CANTER

SPECIFICATIONS

Make FUSO Range Canter FG6-136 TD DWA Mode Model Code EG84PE6RB 12 Axle Layout 4X4 Cab Forward Control Crew 3 seating Vehicle type Freight Carrier Mass Data (kg) GVM Manufacturer's gross vehicle mass 6000 GCM Manufacturer's gross combination mass 7000 Permissible max towing drawing vehicle mass 7000 GA-Front 2600 Manufacturer's front axle mass GA-Rear Manufacturer's rear axle mass 4300 v Permissible maximum vehicle mass 6000 AF 2600 Permissible maximum front axle mass ΔR Permissible maximum rear axle mass 4300 UF Unladen front axle mass 1785 UR Unladen rear axle mass 765 UT (Tare) Total unladen mass 2550 Permissible Body + Payload 3450 Fuel Tank (Litres) Capacity 100 **Dimensions (mm)** OL Overall length 6105 OW Overall width 1995 CA Cab to Axle 2880 ОН Overall height 2435 FOH 1130 Front overhand ROH Rear overhang 1475 WB Wheelbase 3460 Performance Gradeability at Permissible Maximum Weight (V) 60% Maximum Speed (SA Legislation) 100 km/h Minimum turning radius 6.8 m Standard Equipment/features Antilock Braking System (ABS) Exhaust Brake System Lockable Fuel Tank Cap Manual window regulator Outside mirror with long stay Seatbelt for driver, front centre and driver assistant Ashtrav on door for driver and assistant Cigarette lighter Sunvisor for Driver and assistant Interior mirror Heater and defroster Dual type electric horn All lamps with E.e mark Telescopic and tilt steering column with Steering lock Tachometer Standard tool set Limited Slip Differential (LSD)

Low range and High range option (4WD) 2WD and 4WD option (option drive)

Standard Services

4 years / 240 000km warranty

15 000km maintenance schedule

FG6-136 TD DWA

Engine	
Make	FUSC
Model	4D34-2AT
Configuration	4 in lin
Capacity (cm3)	390
Туре	Four stroke water cooled direct injection diesel engin
Power at RPM	100 @ 2,900 - 2,90
Torque at RPM	370 @ 1,600 - 1,60
Emission standards	Euro
Generator	24 Volt, 50 Am
Air Cleaner	Dry paper dual element typ
Suction	Snorkel and rain ca
Governor	All speed mechanical governo
Transmission	· · · · · · · · · · · · · · · · · · ·
Make	FUSC
Model	M035S
Туре	Synchromesh gear
Shift	Manu
No. of gears forward	
Low gear ratio	0.72
High gear ratio	5.38
Clutch	
Make	FUS
Model	C3W2
Туре	Hydraulic Single Dry Plat
Diameter (mm)	27
Drive Axle	
Make	FUS
Model	D033HW/LS
Reduction type	Single reduction, Hypoid ge:
Final Ratio	6.16
	0.10
Suspension	
Front	Laminated leaf springs with shock absorber
Rear	Laminated leaf springs with shock absorber
Steering	
	Telescopic and tilt steering column with steering loc
Brakes	
System type	Hydraulic with vacuum servo assistance, dual circuit with AB
Front	Drur
Rear	Drur
ABS	Ye
Park/Emergency System	Internal Expanding type on propeller sha
Auxiliary Brakes	Exhaust brak
	Exilausi bian
Tyres and Rims	
Tyre Sizes	215/75R17.
Wheel type	Drum Typ
Electrical	
System	24

Simply Better Trucks

DIMENSIONS

www.fuso.co.za









